




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H01Q 1/32	A1	(11) International Publication Number: WO 98/36469 (43) International Publication Date: 20 August 1998 (20.08.98)
<p>(21) International Application Number: PCT/KR98/00029</p> <p>(22) International Filing Date: 16 February 1998 (16.02.98)</p> <p>(30) Priority Data: 1997/4869 18 February 1997 (18.02.97) KR</p> <p>(71) Applicant (for all designated States except US): POONG JEONG INDUSTRIAL CO., LTD. [KR/KR]; 176-1, Do-dang-dong, Wonmi-ku, Puchon-shi, Kyonggi-do 421-130 (KR).</p> <p>(72) Inventors; and (75) Inventors/Applicants (for US only): LEE, Yong Ho [KR/KR]; 929-805 Mokdong Apt., Shinjong 1-dong, Yangchon-ku, Seoul 158-071 (KR). SUNG, Byung, Yong [KR/KR]; 976-6, Shihung 3-dong, Kumchon-ku, Seoul 153-033 (KR).</p> <p>(74) Agent: SUH, Man, Kyu; 3 FL., Jung-An Building, 827-64, Yoksam-dong, Kangnam-ku, Seoul 135-080 (KR).</p>	<p>(81) Designated States: AU, BR, CA, CN, JP, MX, PL, TR, UA, US, UZ, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report.</p>	

(54) Title: ANTENNA DEVICE FOR AUTOMOTIVE VEHICLE

(57) Abstract

The present invention presents an antenna device for an automotive vehicle comprising first coil installed horizontally to receive radio signals, capacitors connected with the first coil in electrical parallel, second coil connected electrically with the first coil and installed horizontally under the first coil, third coil connected electrically between the first coil and the ground and installed horizontally under the first coil, and fourth coil connected electrically between the first coil and the second coil and installed vertically under the first coil, and characterizing that from the first to the fourth coils and capacitors are installed in a mirror case for the car.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakhstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

ANTENNA DEVICE FOR AUTOMOTIVE VEHICLE

BACKGROUND OF THE INVENTION

5 Field of the Invention

 The present invention relates to an antenna device for an automotive vehicle. More particularly, it relates to an antenna device for automotive vehicle, in which the antenna and accompanying elements are installed inside a mirror case for the automotive
10 vehicle, thereby obviating the problem that the antenna is curved by air resistance and increasing reception sensitivity level of radio signals.

Description of the Prior Art

15 Generally, the car has an audio system for providing the driver with information about traffic conditions and comfortable environment. Nowadays, the audio system is installed in a car as a basic part. Drivers can listen to music or news through the car audio system. They can avoid boring conditions due to long drives and
20 select the optimal driving course referring to the traffic news information.

 The audio system requires an antenna to receive radio signals. The dipole antenna is generally installed on the outside of the car and driven by an electric motor.

25 In this conventional dipole antenna, however, there are the problems that the antenna is curved by air resistance when the car is driving at a high speed and reception sensitivity level of radio

signals is lowered.

To solve the problems, an antenna installed in the windshield glass of the car in the form of the pattern is provided. Because the antenna made of copper or silver paster is patterned and formed in
5 the windshield glass, it can not be bent by the wind during the drives.

The antenna formed in the windshield glass has a problem that static electricity produced by friction between the wind and windshield glass is acting as electrical noises thereby the quality
10 of the reception signal is degraded.

SUMMARY OF THE INVENTION

Therefore the object of the present invention is to provide an
15 antenna device for an automotive vehicle, in which an antenna and accompanying elements are installed in a sideview mirror case or a rearview mirror case, thereby obviating the problem that the antenna is curved by air resistance when the car is driving.

The another object of the present invention is to provide an
20 antenna device for an automotive vehicle, in which reception sensitivity level of radio signals is increased by arranging several antennas in vertical and horizontal direction according to the electromagnetic radio wave signals.

The above object has been achieved by the present invention,
25 which provides an antenna device for an automotive vehicle comprising:

a first coil installed horizontally to receive radio signals,

capacitors connected with the first coil in electrical parallel,

a second coil connected electrically with the first coil and installed horizontally under the first coil,

5 a third coil connected electrically between the first coil and the ground and installed horizontally under the first coil, and

a fourth coil connected electrically between the first coil and the second coil and installed vertically under the first coil,

and characterizing that from the first to the fourth coils and
10 capacitors are installed in a mirror case for the automotive vehicle.

Further, according to the present invention, an antenna device for an automotive vehicle is provided, comprising:

a power source for supplying the electrical power;

an antenna for receiving radio signals by means of a cored
15 coil;

a band pass filter for permitting a certain frequency range component of the received signals from the antenna to pass through;

an amplifier for amplifying the filtered signal from the band pass filter;

20 and characterizing that the antenna, the band pass filter and the amplifier are installed in a mirror case for the automotive vehicle.

Additional features and advantages of the invention will be set forth in the description which follows, and in part will be apparent
25 from the description, or may be learned by practice of the invention. The objectives and other advantages of the invention will be realized and attained by the structure particularly pointed out in the written

description and claims hereof as well as the appended drawings.

BRIEF DESCRIPTION OF THE ATTACHED DRAWINGS

5 The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and together with the description serve to explain in the principles of the invention.

10 In the drawings:

FIG.1 is a circuit diagram of an antenna device for automotive vehicle according to the present invention.

15 FIG.2 is a partial cross-sectional view where the antenna device is established in a rear-view mirror according to the present invention.

FIG.3 is a block diagram of an antenna device for automotive vehicle according to another embodiment of the present invention.

FIG.4 is a circuit diagram of the antenna device according to another embodiment of the present invention.

20

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are
25 illustrated in the accompanying drawings.

Referring now to FIG.1 and FIG.2, there is shown the antenna device according to the first embodiment of the present invention.

The first coil L1 is installed horizontally inside a rearview mirror case M. The capacitors C1 and C2 are respectively connected with the first coil L1 in electrical parallel. The second coil L2 is connected electrically with the first coil L1 and installed horizontally under the first coil L1. The third coil L3 is connected electrically between the first coil L1 and the ground and installed horizontally under the first coil L1. The fourth coil L4 is connected electrically between the first coil L1 and the second coil L2 and installed vertically under the first coil L1. The first coil L1, the second coil L2, the third coil L3, the fourth coil L4 and the capacitors C1 and C2 are installed in a mirror case M.

All elements inside the mirror case M is fixed on a printed circuit board and the output terminal of the printed circuit board is connected to a receiving apparatus such as the audio system via a coaxial cable.

The following description relates to the operation of the antenna device according to the first embodiment of the present invention.

When the audio system is powered on, the induced currents are produced in the coils L1 to L4 by the radio broadcasting signal and flow through the coils L1 to L4. The coil antenna can receive the radio broadcasting signal inductively whereas the dipole antenna should contact with the radio signal to receive it.

Intensity of the received signal through the coils L1 to L4 varies in accordance with the kind of core which is rolled by the coil. In the present invention, ferrite, a magnet or a copper pipe can be used as the core.

The signal received by the coils L1 to L4 is transferred to a receiving apparatus such as the audio system through a coaxial cable, thereby the receiving apparatus comes into action.

The performance of the antenna device according to the first embodiment of the present invention can be verified by a numerical expression as follows.

When the antenna is formed of a coil with ferrite bar core which has a radius α , large permeability and turns N, the receiving voltage V_{oc} in AM area is given like the following.

$$V_{oc} = -j\omega\mu_e\mu_oN\pi\alpha^2 H_i = -j(2\pi/\lambda_o)\mu_eN\pi\alpha^2 E_i$$

When the length of the ferrite bar core is very large in comparison with the radius α and permeability is very large over 1, the effective permeability μ_e is obtained like the following.

$$\mu_e = (l/a^2) / (\ln(2l/\alpha) - 1)$$

In the case, the radiating resistance R_a of the antenna is as follows.

$$R_a = 320\pi^6(\gamma_o/\lambda_o)^4N^2\mu_e^2$$

Therefore, when γ_o equals 0.5cm, N equals 100 and $(1/\alpha)$ equals 100, R_a equals 0.0013 Ω and X_a is highly capacitive as the impedance of the antenna at 1MHz.

From above evaluation, it can be found that the antenna device according to the present invention is of good performance in comparison with the dipole antenna.

From now on, the following explanation relates to the second embodiment of the present invention.

Referring to FIG.3 and FIG.4, there is shown the antenna device according to the second embodiment of the present invention.

The power source 10 supplies electric energy. As the power source 10, a small battery cell or a storage battery for the car can be used. The power filter 20 is connected to the power source 10 and filters off electrical noises.

5 The antenna 30 comprises core 31 and the coil 32 wound on the core 31. Ferrite, a magnet or a copper pipe can be used as the core 31.

 The power filter 20 and the antenna 30 are connected to the band pass filter 40. The band pass filter 40 includes the capacitor
10 C41 connected between the output terminal of the power filter 20 and the ground, the coil L41 connected with the output terminal of the filter 20, the capacitor C42 connected between the coil L41 and the ground, the coil L42 connected between the output terminal of the antenna 30 and the ground, the resistor R41 connected between the out
15 put terminal of the antenna 30 and the ground, the capacitor C43 connected with the output terminal of the antenna 30, the operational amplifier A41 connected with the capacitor C43, the capacitor C44 connected with the input terminal of the operational amplifier A41, the capacitor C45 connected to the input terminal of the operational
20 amplifier A41, the resistor R42 connected between the capacitor C45 and the output terminal of the operational amplifier A41, and the capacitor C46 connected between the operational amplifier A41 and the ground.

 The power filter 20 and the band pass filter 40 are connected
25 to the amplifier 50. The amplifier 50 comprises the capacitor C51 connected with the output terminal of the band pass filter 40, the capacitor C52 connected with the capacitor C52, the resistor R51

connected with the capacitor C52, the resistor R52 connected between the capacitor C52 and the ground, and the operational amplifier A51 connected with the capacitor C52.

5 The antenna 30, the band pass filter 40 and the amplifier 50 are installed in the mirror case for the automotive vehicle. All elements inside the mirror case is fixed on a printed circuit board, and the input and output of the printed circuit board is connected to a receiving apparatus like the audio system through a coaxial cable.

10 The following description relates to the operation of the antenna device according to the second embodiment of the present invention.

When a power switch of the audio system turns on, the power source 10 is electrically connected with the power filter 20. The power source supplies the electrical power signal for the power filter 20. The power filter 20 eliminates noises from the power
15 signal. Then, the power filter 20 applies the filtered power signal to the band pass filter 40 and the amplifier 50. When the filtered power signal is applied to the band pass filter 40 and the amplifier 50, they start to work.

20 In the meantime, the induced currents are produced in the antenna 30 by the radio broadcasting signal and applied to the band pass filter 40. The antenna 30 can receive the radio broadcasting signal inductively whereas the dipole antenna should contact with the radio signal to receive it. Intensity of the received signal through
25 the antenna 30 varies in accordance with the kind of core 31.

The band pass filter 40 permits a certain frequency range component of the signals from the antenna 30 to pass through. The

amplifier 50 amplifies the signal from the band pass filter 40, then applies the amplified signal to the audio sytem.

Because the antenna 30, the band pass filter 40 and the amplifier 50 are installed in a mirror case for the car, there is no
5 problem such as the bend due to air resistance during the drives.

As described above, an antenna device where an antenna and accompanying elements are installed in a sideview mirror case or a rearview mirror case is provided. According to the present invention, the antenna device can be prevented from curving due to air
10 resistance when the car is driving, and reception sensitivity of the antenna device can be increased.

It will be apparent to those skilled in the art that various modifications and variations can be made in an antenna device for an automotive vehicle of the present invention without departing from
15 the scope and sprit of the invention. Thus it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.

WHAT IS CLAIMED IS:

1. An antenna device for an automotive vehicle comprising:
a first coil installed horizontally to receive radio
5 signals,
capacitors connected with the first coil in electrical
parallel,
a second coil connected electrically with the first coil and
installed horizontally under the first coil,
10 a third coil connected electrically between the first coil
and a ground and installed horizontally under the first coil, and
a fourth coil connected electrically between the first coil
and the second coil and installed vertically under the first coil,
and characterizing that the first to the fourth coils and
15 capacitors are packed in a mirror for the automotive vehicle.
2. The device as set forth in claim 1, further comprises a
printed circuit board to fix and connect all elements physically and
electrically.
20
3. The device as set forth in claim 1, further comprises the
cores which are rolled by the coil respectively.
4. The device as set forth in claim 3, wherein the core is
25 ferrite.
5. The device as set forth in claim 3, wherein the core is the

magnet.

6. The device as set forth in claim 3, wherein the core is the copper pipe.

5

7. The device as set forth in claim 1, wherein the mirror is the rearview mirror.

10

8. The device as set forth in claim 1, wherein the mirror is the sideview mirror.

15

9. An antenna device for an automotive vehicle comprising:
a power source for supplying the electrical power;
an antenna for receiving radio signals by means of a cored coil;

20

a band pass filter for permitting a certain frequency range component of the received signals from the antenna to pass through;
an amplifier for amplifying the filtered signal from the band pass filter;
and characterizing that the antenna, the band pass filter and the amplifier are installed in a mirror case for the automotive vehicle.

25

10. The device as set forth in claim 9, further comprises a printed circuit board to fix and connect all elements physically and electrically.

11. The device as set forth in claim 9, where in the antenna includes a core and the coil wound on the core.

12. The device as set forth in claim 11, wherein the core is
5 ferrite.


13. The device as set forth in claim 11, wherein the core is the magnet.

10 14. The device as set forth in claim 11, wherein the core is the copper pipe.


15 15. The device as set forth in claim 9, wherein the mirror is the rearview mirror.

16. The device as set forth in claim 9, wherein the mirror is the sideview mirror.


1 / 4
FIG. 1



214
FIG. 2




3/4
FIG. 3



4/4

FIG. 4



INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR. 98/00029

A. CLASSIFICATION OF SUBJECT MATTER

IPC⁶: H 01 Q 1/32

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC⁶: H 01 Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPI, EPODOC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4 760 394 A (TAKEUCHI et al.) 26 July 1988 (16.07.88), totality.	1-16
A	US 5 504 478 A (KANPP-GENTEX) 02 April 1996 (02.04.96), totality.	1-16
A	EP 0 540 899 B1 (TELEVES) 24 August 1994 (24.08.94), totality.	1-16
A	AU 68 074/65 A (VAN BEMMEL) 20 June 1968 (20.06.68), fig.1.	1-16
A	DE 2 425 189 A (SACHAROW et al.) 19 December 1974 (19.12.74), fig.2,3.	1-16

☐ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination, being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

11 May 1998 (11.05.98)

Date of mailing of the international search report

15 May 1998 (15.05.98)

Name and mailing address of the ISA/ AT
 AUSTRIAN PATENT OFFICE
 Kohlmarkt 8-10
 A-1014 Vienna
 Facsimile No. 1/53424/535

Authorized officer

Heinich

Telephone No. 1/53424/454

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/KR 98/00029

In Recherchenbericht angeführtes Patentdokument Patent document cited in search report Document de brevet cité dans le rapport de recherche	Datum der Veröffentlichung Publication date Date de publication	Mitglied(er) der Patentfamilie Patent family member(s) Membre(s) de la famille de brevets	Datum der Veröffentlichung Publication date Date de publication
US A 4760394	26-07-88	DE A1 3627193 DE C2 3627193 JP A2 62038004 JP B4 6038562	19-02-87 07-12-89 19-02-87 18-05-94
US A 5504478	02-04-96	CA AA 2125101 WD A1 9519598	13-07-95 20-07-95
EP B1 540899		ES UA 1018092 ES YA 1018092	01-01-92 16-07-92
AU A 68074		keine - none - rien	
DE A 2425189		CS B 182373 DE A1 2425189 FR A1 2231124 FR B1 2231124 HU F 170360 IT A 1034054	28-04-78 19-12-74 20-12-74 07-07-78 28-05-77 10-09-79

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.